

MARIANO FARRUGIA

TESSUTI



KENIA

CARACTERÍSTICAS TÉCNICAS / TECHNICAL DETAILS

Código aduanero / Customs code		59031090
Código alfanumérico artículo / Alphanumeric article code		02039 FPL
Composición / Composition		84% PVC - 16% CO
Ancho / Width	UNI EN 1773	137 cm.
Peso / Weight	UNI 5114	700 gr/m² ±5%
Espesor / Thickness		1,3 mm ±0,2 mm
Longitud pieza / Roll length		±30 mt
Solidez del color al frote Colour fastness to rubbing	CROCK METER ISO 105 X 12	4/5 SECO - DRY 4/5 HÚMEDO - WET
Solidez del color a la luz artificial Colour fastness to artificial light	XENO ISO 105 B 02	≥ 5
Resistencia a la tracción Tensile resistance	ISO 1421	≥ 24 N5cm URDIMBRE - WARP ≥ 15 N5cm TRAMA - WEFT
Resistencia a la rotura Extension at break	ISO 1421	≥ 13% LARGO - LENGTH ≥ 10% ANCHO - WIDTH
Flexión ciclos / Flexion cycles	ISO 4818 - P13	> 150.000 BALLY
Resistencia a la abrasión / Abrasion resistance	ISO 5470-2	> 75.000 MARTINDALE
Cumple con / Passes	REACH standard	
Comportamiento frente al fuego / Fire retardant	ITALIA / ITALY EUROPA / EUROPE INGLATERRA - HOGAR ENGLAND - DOMESTIC INGLATERRA - CONTRACT ENGLAND - CONTRACT ALEMANIA / GERMANY FRANCIA / FRANCE EE.UU. / U.S.A. NAUTICA / NAUTICAL	UNI 9175 Class 11M EN 1021 part 1-2 BS 5852:79 IS 0-1 BS 5852:06 IS 11 (CRIB 5) DIN 4102-1 (B1) NF-P 92 503 (M1) California TB:117 2013 FTP Code 307 Part 8
Símbolos de cuidado y limpieza / Care label	UNI EN ISO 3758	

Estos valores se dan únicamente para información de buena fe y no pueden considerarse en ningún caso vinculantes. No se responde del uso inapropiado. **Se permiten ligeras diferencias de color entre diferentes lotes.** The overmentioned data correspond to average values communicated in good faith, but they cannot be considered as a contract document. The company is not responsible for any inappropriate use of the product. **Slight colour differences among several lots are admitted.**

www.mfarrugia.com

info@mfarrugia.com

+34 968 75 10 39 FAX +34 968 79 26 72